

BEST AVAILABLE COPY

Amendments to the Claims:

This listing of claims will replace all prior versions, and listings of claims in the application:

Please cancel claims 1, 9, and 17 without prejudice or disclaimer.

This listing of claims will replace all prior versions, and listings of claims in the application:

1. (Canceled)

²
~~2~~. (Previously Presented) The cam assembly according to claim ¹~~4~~, wherein said sliding member further has a face slot defined thereon to retain said cam.

³
~~3~~. (Previously Presented) The cam assembly according to claim ¹~~4~~, wherein the cam includes a washer and a nut.

¹
~~4~~. (Previously Presented) A cam assembly for mounting on a stationary member, comprising:

- (a) a sliding member having a first slot defined therethrough;
- (b) a cam;
- (c) a first fastener that extends through said first slot in said sliding member to said stationary member; and

a second fastener that extends through a second slot in said sliding member to said stationary member, wherein said cam is operably coupled to said sliding member to direct longitudinal movement along said stationary member when said cam is rotated.

⁴
~~5.~~ (Previously Presented) A cam assembly for mounting on a stationary member, comprising:

- (a) a sliding member having a first slot defined therethrough;
- (b) a cam; and
- (c) a first fastener that extends through said first slot in said sliding member to said stationary member, wherein said cam is operably coupled to said sliding member to direct longitudinal movement along said stationary member when said cam is rotated and said first fastener and a second fastener comprise a head.

⁵
~~6.~~ (Previously Presented) A cam assembly for mounting on a stationary member, comprising:

- (a) a sliding member having a first slot defined therethrough;
- (b) a cam; and
- (c) a first fastener that extends through said first slot in said sliding member to said stationary member, wherein said cam is operably coupled to said sliding member to direct longitudinal movement along said stationary member when said cam is rotated and said first fastener and a second fastener comprise a head, which has a configuration that is one of hex, six-point, eight-point, ten-point, twelve-point and torx configurations.

⁶
~~7.~~ (Previously Presented) The cam assembly according to claim ¹~~4~~, wherein the stationary member is fitted with threads that mate with threads of the first and second fasteners.

⁷
~~8.~~ (Previously Presented) The cam assembly according to claim ¹~~4~~, wherein the stationary member has nuts fitted with threads that mate with threads of the first and second fasteners.

9. (Canceled)

⁹
~~10~~. (Previously Presented) The method according to claim ⁸~~12~~, wherein said sliding member further has a face slot defined thereon to retain said cam.

¹⁰
~~11~~. (Previously Presented) The method according to claim ⁸~~12~~, wherein the cam includes a washer and a nut.

⁸
~~12~~. (Previously Presented) A method of making a position adjustment between a sliding member and a stationary member, comprising:

- (a) rotating a cam;
- (b) sliding a sliding member having a first slot defined therethrough and a second fastener that extends through a second slot in said sliding member to said stationary member; and
- (c) tightening a first fastener that extends through said first slot in said sliding member to said stationary member, wherein said cam is operably coupled to said sliding member to direct longitudinal movement along said stationary member when said cam is rotated.

¹¹
~~13~~. (Previously Presented) A method of making a position adjustment between a sliding member and a stationary member, comprising:

- (a) rotating a cam;
- (b) sliding a sliding member having a first slot defined therethrough; and
- (c) tightening a first fastener that extends through said first slot in said sliding member to said stationary member, wherein said cam is operably coupled to said sliding member to direct longitudinal movement along said stationary member when said cam is rotated and said first fastener and a second fastener comprise a head.

¹²
~~14~~. (Previously Presented) A method of making a position adjustment between a sliding member and a stationary member, comprising:

- (a) rotating a cam;
- (b) sliding a sliding member having a first slot defined therethrough; and
- (c) tightening a first fastener that extends through said first slot in said sliding member to said stationary member, wherein said cam is operably coupled to said sliding member to direct longitudinal movement along said stationary member when said cam is rotated and said first fastener and a second fastener comprise a head, which has a configuration that is one of hex, six-point, eight-point, ten-point, twelve-point and torx configurations.

¹³ ⁸
~~15~~. (Previously Presented) The method according to claim ~~12~~, wherein the stationary member is fitted with threads that mate with threads of the first and second fasteners.

¹⁴ ⁸
~~16~~. (Previously Presented) The method according to claim ~~12~~, wherein the stationary member has nuts fitted with threads that mate with threads of the first and second fasteners.

17. (Canceled)

¹⁶ ¹⁵
~~18~~. (Currently Amended) The ~~adjustment means~~ apparatus according to claim ~~20~~, wherein said sliding means further has a face slot defined thereon to retain said camming means.

¹⁷ ¹⁵
~~19~~. (Currently Amended) The ~~adjustment means~~ apparatus according to claim ~~20~~, wherein the camming means includes a washer and a nut.

¹⁵
20. (Currently Amended) ~~A means~~ An apparatus for making a position adjustment between a sliding member and a stationary member, comprising:

- (a) a sliding means having a first slot defined therethrough;
- (b) a camming means;
- (c) a first fastening means that extends through said first slot in said sliding means to said stationary member; and
- (d) a second fastening means that extends through a second slot in said sliding means to said stationary member, wherein said camming means is operably coupled to said sliding means to direct longitudinal movement along said stationary member when said camming means is rotated.

¹⁵
¹⁵
21. (Currently Amended) The ~~adjustment means~~ apparatus according to claim 20, wherein the stationary means is fitted with threads that mate with threads of the first and second fastening means.

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ **BLACK BORDERS**
- ☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**
- ☐ **FADED TEXT OR DRAWING**
- ☐ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**
- ☐ **SKEWED/SLANTED IMAGES**
- ☐ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**
- ☐ **GRAY SCALE DOCUMENTS**
- ☐ **LINES OR MARKS ON ORIGINAL DOCUMENT**
- ☐ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**
- ☐ **OTHER:** _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.